



C Series

C50S/C50SS/C70S/C70SS/C90S Trailer Mounted Concrete Pumps



C Series:

REED C Series pumps feature Rexroth "Closed-Loop" hydraulic systems, twin axles and twin-shift cylinders. These high-performance pumps excel even under the most extreme conditions. **REED** is the first trailer pump manufacturer to bring this top-level Boom Pump technology to trailer pumps.

The rugged, powerful **C Series** pumps are designed to withstand the punishment inherent to heavy construction environments.

Superior engineering, premium technology, top quality components and pride in workmanship make **C Series** pumps the most reliable pumps on the market.

Standard Features:

- **Rexroth** Closed-loop, over-center hydraulic system
- **Cummins Diesel Engines** are Powerful (more torque), Quieter, and more Efficient (lower RPMs). EPA Tier 3 approval
- **REED PLC (Programmable Logic Controller)** Allows for self diagnosis on the LCD, simple adjustments, and future enhancements
- **Variable-volume** and **R.P.M. control** at remote control box
- **Strongest Shifting Cylinder Force** on the market
- **Carbide Wear Parts**
- Hydraulic Outriggers
- Super heavy-duty frame (sturdiest frame on market)
- Twin axle trailer 2x7000 lb (2x3182 kg)
- 3" Splined shaft on heavy-duty "S"-tube
- 42" stroke length
- Special high-pressure reinforced hopper

C Series

C50S/C50SS/C70S/C70SS/C90S Trailer Mounted Concrete Pumps

Additional Features:

- Adjustable Shifting Force Valve
- Stainless-steel hopper splash guard
- Hard chromed concrete cylinders
- Large fuel tank capacity with gauge
- Weatherproof NEMA 4 control panel
- High capacity hydraulic oil cooler
- Remote Control with 50' (15m) Cable
 - On/Off, b) Forward-Reverse,
 - Stroke Change (S-tube Jog),
 - Engine RPM Control, e) Hydraulic Pump Volume Control
- Hour meter/tachometer
- Reversibility at any point in the stroke
- Safety Emergency Stop Function
- 3" Diameter Splined shaft on "S" Valve
- E.P.A. Tier 3 Approval of Cummins Diesel Engines
- Highest commonality of hydraulic hoses
- Hopper grate

Optional Features:

- Radio remote control
- Hydraulically driven water wash-out pump
- Vibrator for hopper screen
- Chemical additive pump
- Stroke counter
- Skid mounting
- Lifting eyes
- "Murphy" switch for engine
- Electric motor instead of diesel
- Surge brakes

MODEL			C50S	C50SS	C70S	C70SS	C90S	
							H.V.	H.P.
Concrete Output	yd ³ /hr		50	54	70	74	90	74
	m ³ /hr		38	41	54	556	69	56
Concrete Pressure	psi		1640	2000	1125	1469	896	1469
	bar		114	138	78	102	62	102
Horizontal Pumping Distance*	ft		1425*	2000*	1000*	1350*	1000*	1350*
	m		434*	610*	305*	411*	305*	411*
Vertical Pumping Distance*	ft		575*	800*	425*	550*	550*	425*
	m		175*	244*	130*	168*	168*	130*
Cummins Diesel Engine (Tier 3 Approved)	hp		160	220	160	220	220	220
	kW		119	164	119	164	164	164
Concrete Cylinder Diameter	in		6"	6"	7"	7"	7"	7"
	mm		152	152	175	175	175	175
Stroke Length	in		42"	42"	42"	42"	42"	42"
	mm		1067	1067	1067	1067	1067	1067
Maximum Aggregate Size	in		1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
	mm		38	38	38	38	38	38
Hopper Capacity (Standard)	ft ³		12	12	not avail.	not avail.	not avail.	not avail.
	liters		340	340	not avail.	not avail.	not avail.	not avail.
Hopper Capacity (Harsh-Mix)	ft ³		not avail.	not avail.	14.5	14.5	14.5	14.5
	liters		not avail.	not avail.	410	410	410	410
Hopper Height (Standard)	in		44"	44"	not avail.	not avail.	not avail.	not avail.
	mm		1118	1118	not avail.	not avail.	not avail.	not avail.
Hopper Height (Harsh-Mix)	in		not avail.	not avail.	47"	47"	47"	47"
	mm		not avail.	not avail.	1194	1194	1194	1194
Hydraulic Oil Capacity	gal		60	60	60	60	60	60
	liters		227	227	227	227	227	227
Fuel Capacity	gal		39	39	39	39	39	39
	liters		148	148	148	148	148	148
Outlet Size	in		5"	5"	5"	5"	5"	5"
	mm		127	127	127	127	127	127
Dimensions	in	Length	184"	Width	71"	Height	83"	
	mm		4674		1803		2108	
Weight (Approx.) (with oil and fuel)	lbs		8260	8260	8600	8600	8750	8750
	kg		3755	3755	3909	3909	3977	3977

* Theoretical distances and performance shown above are estimated using standard industry methods. Actual performance will vary depending on the concrete pump (concrete pressure, horsepower), material (mix design, slump, local sand and rock characteristics), and delivery system (pipeline diameter, type (steel or hose) and reductions/bends). Maximum output, pressure, and distance cannot be reached simultaneously. Specifications subject to change without prior notice.



Distributed By:

REED can truck or skid mount any concrete pump.
(consult factory for details)

REED • An Independent Member of the Shea Family of Companies
13822 Oaks Avenue • Chino, California 91710-7008 USA • 909-287-2100
Fax: 909-287-2140 • Toll-free: 888-779-7333 • www.reedpumps.com